

CPVC reducing bushing



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
1" x 3/4"	25 x 20	33.4 x 26.7	Sch40 / Sch80	Spigot x Socket	175	PL5401 (UL/FM)
1-1/4" x 1"	32 x 25	42.2 x 33.4	Sch40 / Sch80	Spigot x Socket	175	PL5402 (UL/FM)
1-1/4" x 3/4"	32 x 20	42.2 x 26.7	Sch40 / Sch80	Spigot x Socket	175	PL5403 (UL/FM)
1-1/2" x 1-1/4"	40 x 32	48.3 x 42.2	Sch40 / Sch80	Spigot x Socket	175	PL5404 (UL/FM)
1-1/2" x 1"	40 x 25	48.3 x 33.4	Sch40 / Sch80	Spigot x Socket	175	PL5405 (UL/FM)
1-1/2" x 3/4"	40 x 20	48.3 x 26.7	Sch40 / Sch80	Spigot x Socket	175	PL5406 (UL/FM)
2" x 1-1/2"	50 x 40	60.3 x 48.3	Sch40 / Sch80	Spigot x Socket	175	PL5407 (UL/FM)
2" x 1-1/4"	50 x 32	60.3 x 42.2	Sch40 / Sch80	Spigot x Socket	175	PL5408 (UL/FM)
2" x 1"	50 x 25	60.3 x 33.4	Sch40 / Sch80	Spigot x Socket	175	PL5409 (UL/FM)
2" x 3/4"	50 x 20	60.3 x 26.7	Sch40 / Sch80	Spigot x Socket	175	PL5410 (UL/FM)
2-1/2" x 2"	65 x 50	73.0 x 60.3	Sch40 / Sch80	Spigot x Socket	175	PL5411 (UL/FM)
2-1/2" x 1-1/2"	65 x 40	73.0 x 48.3	Sch40 / Sch80	Spigot x Socket	175	PL5412 (UL/FM)
2-1/2" x 1-1/4"	65 x 32	73.0 x 42.2	Sch40 / Sch80	Spigot x Socket	175	PL5413 (UL/FM)
2-1/2" x 1"	65 x 25	73.0 x 33.4	Sch40 / Sch80	Spigot x Socket	175	PL5414 (UL/FM)
3" x 2-1/2"	80 x 65	88.9 x 73.0	Sch40 / Sch80	Spigot x Socket	175	PL5415 (UL/FM)
3" x 2"	80 x 50	88.9 x 60.3	Sch40 / Sch80	Spigot x Socket	175	PL5416 (UL/FM)