

CPVC socket flange



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Flanged end: Per ANSI B16.1 Class 125, B16.42 Class 150, FF or RF
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)

Available size

Size			Bolting for mating flange		Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)	PCD (mm)	Bolt			
2"	50	60.3	120.7	4 x 5/8"	Socket x FLG	175	PL5505 (UL/FM)
2-1/2"	65	73.0	139.7	4 x 5/8"	Socket x FLG	175	PL5506 (UL/FM)
3"	80	88.9	152.4	4 x 5/8"	Socket x FLG	175	PL5507 (UL/FM)

CPVC blind flange



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC, inherently flame-retardant
- Flanged end: Per ANSI B16.1 Class 125, B16.42 Class 150, FF or RF
- Color: Orange (RAL 2004)

Available size

Size			Bolting for mating flange		Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)	PCD (mm)	Bolt			
2"	50	60.3	120.7	4 x 5/8"	FLG	175	PL5605 (UL/FM)
2-1/2"	65	73.0	139.7	4 x 5/8"	FLG	175	PL5606 (UL/FM)
3"	80	88.9	152.4	4 x 5/8"	FLG	175	PL5607 (UL/FM)