

CPVC adapter (Socket x FIPT)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4"	20	26.7	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6101 (UL/FM)
1"	25	33.4	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6102 (UL/FM)
1-1/4"	32	42.2	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6103 (UL/FM)
1-1/2"	40	48.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6104 (UL/FM)
2"	50	60.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6105 (UL/FM)

CPVC adapter (Spigot x FIPT)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4"	20	26.7	Sch40 / Sch80	Spigot x FNPT	175	PL6201 (UL/FM)
1"	25	33.4	Sch40 / Sch80	Spigot x FNPT	175	PL6202 (UL/FM)