

CPVC sprinkler head adapter (Socket x FIPT)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4" x 1/2"	20 x 15	26.7 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6401 (UL/FM)
1" x 1/2"	25 x 15	33.4 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6402 (UL/FM)
1" x 3/4"	25 x 20	33.4 x 26.7	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6403 (UL/FM)

CPVC sprinkler head adapter (Spigot x FIPT)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4" x 1/2"	20 x 15	26.7 x 21.3	Sch40 / Sch80	Spigot x FNPT / FBSPT	175	PL6501 (UL/FM)
1" x 1/2"	25 x 15	33.4 x 21.3	Sch40 / Sch80	Spigot x FNPT / FBSPT	175	PL6502 (UL/FM)