

CPVC sprinkler adapter elbow (Socket x FIPT)



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4" x 1/2"	20 x 15	26.7 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6601 (UL/FM)
1" x 1/2"	25 x 15	33.4 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6602 (UL/FM)
1" x 3/4"	25 x 20	33.4 x 26.7	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6603 (UL/FM)
1-1/4" x 1/2"	32 x 15	42.2 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6604 (UL/FM)

CPVC female threaded sprinkler adapter tee



- Certificate: UL Listed / FM Approved
- Standard: UL 1821, ASTM F438, ASTM F439
- Material: CPVC + brass insert
- Temperature: Max 150°F (66°C), ambient
- Color: Orange (RAL 2004)



Available size

Size			Thickness	Connection	Working pressure (psi)	Ref. No.
NPS	DN	Ave. OD (mm)				
3/4" x 3/4" x 1/2"	20 x 20 x 15	26.7 x 26.7 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6701 (UL/FM)
1" x 1" x 1/2"	25 x 25 x 15	33.4 x 33.4 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6702 (UL/FM)
1" x 1" x 1"	25 x 25 x 25	33.4 x 33.4 x 33.4	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6703 (UL/FM)
1-1/4" x 1-1/4" x 1/2"	32 x 32 x 15	42.2 x 42.2 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6704 (UL/FM)
1-1/2" x 1-1/2" x 1/2"	40 x 40 x 15	48.3 x 48.3 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6705 (UL/FM)
2" x 2" x 1/2"	50 x 50 x 15	60.3 x 60.3 x 21.3	Sch40 / Sch80	Socket x FNPT / FBSPT	175	PL6706 (UL/FM)

PL66-67 /