

Orifice plates



- Certificate: ISO
- Standard: ISO 5167-2, GB 50084
- Material: SS304 / SS316L
- Feature: Simply reduce residual pressure
- Surface: Bright SS surface

Available size

| Piping size | Orifice (mm) | Thickness (mm) | Connection | Installation spool | Working pressure (bar) | Ref. No. |
|--------------|--------------|----------------|------------|--------------------|------------------------|----------|
| DN 50 (2") | 12.5 ~ 40 | 3 | Wafer | Yes / no | 16 | FE7501 |
| DN 65 (2.5") | 12.5 ~ 50 | 3 | Wafer | Yes / no | 16 | FE7502 |
| DN 80 (3") | 12.5 ~ 60 | 3 | Wafer | Yes / no | 16 | FE7503 |
| DN 100 (4") | 12.5 ~ 80 | 6 | Wafer | Yes / no | 16 | FE7504 |
| DN 125 (5") | 12.5 ~ 100 | 6 | Wafer | Yes / no | 16 | FE7505 |
| DN 150 (6") | 15 ~ 120 | 6 | Wafer | Yes / no | 16 | FE7506 |
| DN 200 (8") | 20 ~ 160 | 9 | Wafer | Yes / no | 16 | FE7507 |
| DN 250 (10") | 25 ~ 200 | 9 | Wafer | Yes / no | 16 | FE7508 |

Note: Orifice size and thickness can be customized.



Fire hose reel cover

- Certificate: ISO
- Standard: Refer to NFPA 701
- Material: Polyester, PVC, etc.
- Feature: Waterproof, dustproof, UV resistant
- Color: Red, gray, yellow, or customized

Available size

| Shape | Material | Application | Dimension (mm) | Ref. No. |
|-------|---------------------|---|-----------------|----------|
| Round | Polyester + PVC | For fire hose reel max size 1" x 30m, elastic back | 630 x 270 | FE7601 |
| Door | Flame Retardant PVC | For fire hose reel max size 1" x 30m, hook-and-loop closure | 620 x 570 x 230 | FE7602 |

Note: Size, marking and logo can be customized.