



Fire blanket

- Certificate: LPCB Approved
- Standard: BS EN 1869
- Material: Fire-retardant fiberglass
- Feature: Fight small fire
- Surface: White, fold in plastic box

Available size

Dimension (m)	Temperature resistance (°C)	Thickness (mm)	Approx. weight (kg)	Coating	Ref. No.
1.2 x 1.2	280 ~ 550	0.25 ~ 0.43	0.6	Silicone	FE8701 (LPCB)
1.2 x 1.8	280 ~ 550	0.25 ~ 0.43	0.9	Silicone	FE8702 (LPCB)
1.5 x 1.8	280 ~ 550	0.25 ~ 0.43	1.1	Silicone	FE8703 (LPCB)
1.8 x 1.8	280 ~ 550	0.25 ~ 0.43	1.6	Silicone	FE8704 (ISO)
4 x 4	280 ~ 550	0.25 ~ 0.43	11	Silicone	FE8705 (ISO)
6 x 9	280 ~ 550	0.25 ~ 0.43	32	Silicone	FE8706 (ISO)



Fire extinguisher ball

- Certificate: ISO
- Standard: Refer to GA602
- Fire rating: Class A, B and C fire
- Agent: ABC dry powder
- Surface: Red, with mounting bracket

Available size

Capacity (kg)	Diameter (mm)	Effective area (m³)	Response time (s)	Alarm loudness (db)	Ref. No.
0.5	125	1.0	3 ~ 10	≤100	FE8801
1.3	150	2.5	3 ~ 10	≤100	FE8802
2.5	180	7.0	3 ~ 10	≤100	FE8803
4	226	9.0	3 ~ 10	≤100	FE8804