


Grooved 90° reducing elbow with female threaded outlet



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
- Thread run: Female thread, NPT / BSPT
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized



Available size

Size			Center to end, L (mm)		Ref. No.
Inch	DN	mm	L1	L2	
1-1/4" x 1/2"	32 x 15	42.4 x 21.3	35	45	G0601
1-1/4" x 3/4"	32 x 20	42.4 x 26.9	35	48	G0602
1-1/4" x 1"	32 x 25	42.4 x 33.7	39	52	G0603
1-1/2" x 1/2"	40 x 15	48.3 x 21.3	35	45	G0604
1-1/2" x 3/4"	40 x 20	48.3 x 26.9	35	48	G0605
1-1/2" x 1"	40 x 25	48.3 x 33.7	39	52	G0606
2" x 1/2"	50 x 15	60.3 x 21.3	41	45	G0607
2" x 3/4"	50 x 20	60.3 x 26.9	41	48	G0608
2" x 1"	50 x 25	60.3 x 33.7	45	52	G0609
2-1/2" x 3/4"	65 x 20	73.0 x 26.9	46	48	G0610
2-1/2" x 1"	65 x 25	73.0 x 33.7	49	52	G0611
3" x 3/4"	80 x 20	88.9 x 26.9	60	52	G0612
3" x 1"	80 x 25	88.9 x 33.7	64	52	G0613