


Light duty clevis hanger

Light duty clevis hanger from TPMC features a two-part assembly with a formed U-strap supporting the pipe from beneath and an upper yoke secured by a cross bolt. The design provides reliable load capacity, rigidity, and easy vertical adjustment via the hanger rod connection, while reducing rod bending by allowing limited horizontal swing along the pipe axis. UL Listed, this light duty clevis hanger is ideal for suspending non-insulated stationary horizontal steel or CPVC piping in branch lines and smaller main lines of fire sprinkler systems.



- Certificate: UL Listed
- Standard: UL 203, MSS SP-58 (Type 1), MSS SP-69
- Material: Carbon steel
- Temperature: Max 232°C
- Surface: Pre-galvanized / electro-galvanized / hot-dip galvanized
- Application: Suspend non-insulated carbon steel, copper, CPVC piping



Available sizes (Plain edge)

Pipe size		Rod size (RS)		Dimension (mm)		Max rec. load (lbs)	Ref. No.
NPS	DN	Imperial	Metric	A	B		
1/2"	15	3/8"	M10	55	42	150	P4201 (UL)
3/4"	20	3/8"	M10	60	44	250	P4202 (UL)
1"	25	3/8"	M10	69	50	250	P4203 (UL)
1-1/4"	32	3/8"	M10	84	61	250	P4204 (UL)
1-1/2"	40	3/8"	M10	99	61	250	P4205 (UL)
2"	50	3/8"	M10	115	69	250	P4206 (UL)
2-1/2"	65	1/2"	M12	131	77	350	P4207 (UL)
3"	80	1/2"	M12	168	90	350	P4208 (UL)
4"	100	1/2" or 5/8"	M12 or M16	198	114	400	P4209 (UL)

Note: Load ratings are calculated with a minimum safety factor of 5:1 and apply at normal ambient temperatures. Values are based on the lesser of hanger rod tensile strength and clevis assembly capacity. For critical applications, consult project engineering specifications.

Light duty clevis hanger

Available sizes (Flared edge)

Pipe size		Rod size (RS)		Dimension (mm)		Max rec. load (lbs)	Ref. No.
NPS	DN	Imperial	Metric	A	B		
1/2"	15	3/8"	M10	59	45	150	P4221 (UL)
3/4"	20	3/8"	M10	64	48	150	P4222 (UL)
1"	25	3/8"	M10	71	51	250	P4223 (UL)
1-1/4"	32	3/8"	M10	80	56	250	P4224 (UL)
1-1/2"	40	3/8"	M10	94	67	250	P4225 (UL)
2"	50	3/8"	M10	110	77	250	P4226 (UL)
2-1/2"	65	1/2"	M12	134	95	350	P4227 (UL)
3"	80	1/2"	M12	154	107	350	P4228 (UL)
4"	100	5/8"	M16	189	129	500	P4229 (UL)

Note: Load ratings are calculated with a minimum safety factor of 5:1 and apply at normal ambient temperatures. Values are based on the lesser of hanger rod tensile strength and clevis assembly capacity. For critical applications, consult project engineering specifications.