


## Swivel loop hanger (Band hanger)

Swivel loop hanger (Band hanger) from TPMC features a formed steel strap looped around the pipe circumference, providing a broad bearing surface to prevent point-loading damage. A knurled swivel nut engages the hanger rod, permitting precise on-site vertical adjustment and lateral swing to accommodate minor misalignment and thermal expansion.

UL Listed and FM Approved, this hanger is ideal for the suspension of non-insulated stationary horizontal piping in light duty commercial and industrial applications.



- Certificate: UL Listed / FM Approved
- Standard: UL 203, MSS SP-58 (Type 10), MSS SP-69
- Material: Carbon steel
- Temperature: Max 232°C
- Surface: Pre-galvanized / electro-galvanized
- Application: Suspend non-insulated carbon steel, copper, CPVC piping



### Available sizes

| Pipe size |     | Rod size (RS) |        | Dimension (mm) |     | Max rec. load (lbs) | Ref. No.      |
|-----------|-----|---------------|--------|----------------|-----|---------------------|---------------|
| NPS       | DN  | Imperial      | Metric | A              | B   |                     |               |
| 1/2"      | 15  | 3/8"          | M10    | 70             | 40  | 300                 | P4601 (UL)    |
| 3/4"      | 20  | 3/8"          | M10    | 78             | 45  | 300                 | P4602 (UL/FM) |
| 1"        | 25  | 3/8"          | M10    | 84             | 48  | 300                 | P4603 (UL/FM) |
| 1-1/4"    | 32  | 3/8"          | M10    | 90             | 50  | 300                 | P4604 (UL/FM) |
| 1-1/2"    | 40  | 3/8"          | M10    | 98             | 55  | 300                 | P4605 (UL/FM) |
| 2"        | 50  | 3/8"          | M10    | 109            | 60  | 300                 | P4606 (UL/FM) |
| 2-1/2"    | 65  | 3/8"          | M10    | 132            | 78  | 525                 | P4607 (UL/FM) |
| 3"        | 80  | 3/8"          | M10    | 145            | 82  | 525                 | P4608 (UL/FM) |
| 4"        | 100 | 3/8"          | M10    | 175            | 100 | 650                 | P4609 (UL/FM) |
| 5"        | 125 | 1/2"          | M12    | 210            | 116 | 1000                | P4610 (UL/FM) |

# Swivel loop hanger (Band hanger)

## Available sizes

| Pipe size |     | Rod size (RS) |        | Dimension (mm) |     | Max rec. load (lbs) | Ref. No.      |
|-----------|-----|---------------|--------|----------------|-----|---------------------|---------------|
| NPS       | DN  | Imperial      | Metric | A              | B   |                     |               |
| 6"        | 150 | 1/2"          | M12    | 245            | 135 | 1000                | P4611 (UL/FM) |
| 8"        | 200 | 1/2"          | M12    | 315            | 183 | 1000                | P4612 (UL/FM) |
| 10"       | 250 | 5/8"          | M16    | 397            | 226 | 2000                | P4613 (UL/FM) |
| 12"       | 300 | 5/8"          | M16    | 468            | 272 | 3000                | P4614 (UL/FM) |

**Note:** Load ratings are calculated with a minimum safety factor of 5:1 and apply at normal ambient temperatures. Values are based on the lesser of hanger rod tensile strength and band assembly capacity. For critical applications, consult project engineering specifications.