


Eye socket




- Certificate: ISO
- Standard: UL 203, MSS SP-58 (Type 16), MSS SP-69
- Material: Malleable iron
- Temperature: Max 232°C
- Thread: Imperial, UNC, Class 2B per ASME B1.1
Metric, coarse thread, 6g per ISO 965-1
- Surface: Pre-galvanized / electro-galvanized

Available sizes

Rod size (RS)		Max bolt size B	Length E (mm)	Max rec. load (lbs)	Ref. No.
Imperial	Metric				
3/8"	M10	1/4"	35	730	P5701 (ISO)
1/2"	M12	1/4"	38	1350	P5702 (ISO)
5/8"	M16	3/8"	44	1580	P5703 (ISO)
3/4"	M20	1/2"	51	1900	P5704 (ISO)
7/8"	M22	1/2"	60	2200	P5705 (ISO)

Note: Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.

Turnbuckle adjuster (Hanger adjuster)



- Certificate: ISO
- Standard: UL 203, MSS SP-58 (Type 15), MSS SP-69
- Material: Malleable iron
- Temperature: Max 232°C
- Thread: Imperial, UNC, Class 2B per ASME B1.1
Metric, coarse thread, 6g per ISO 965-1
- Surface: Pre-galvanized / electro-galvanized

Available sizes

Rod size (RS)		Eye ring H	Length E (mm)	Max rec. load (lbs)	Ref. No.
Imperial	Metric				
3/8"	M10	13/32"	98	730	P5801 (ISO)
1/2"	M12	13/32"	98	730	P5802 (ISO)
5/8"	M16	1/2"	130	730	P5803 (ISO)
3/4"	M20	1/2"	130	860	P5804 (ISO)

Note: Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.