


Universal beam clamp



- Certificate: UL Listed / FM Approved
- Standard: UL 203, MSS SP-58 (Type 19 & 23), MSS SP-69
- Material: Ductile iron, with hardened steel cup-point set screw and locknut
- Surface: Plain / electro-galvanized
- Application: Attach to top or bottom flanges of structural steel members




Available sizes

Rod size (RS)		Dimension (mm)		Set screw size	Max rec. load (lbs)		Ref. No.
Imperial	Metric	A	B		Top	Bottom	
3/8"	M10	19	47	3/8" (M10)	500	250	P6101 (UL/FM)
1/2"	M12	19	58	1/2" (M12)	950	760	P6102 (UL/FM)

Note:

1. Set screw must be tightened onto the sloped side of the beam flange. Follow recommended torque values per MSS SP-69.
2. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.

Wide mouth beam clamp



- Certificate: UL Listed / FM Approved
- Standard: UL 203, MSS SP-58 (Type 19), MSS SP-69
- Material: Ductile iron, with hardened steel cup-point set screw and locknut
- Surface: Plain / electro-galvanized
- Application: Attach to top or bottom flanges of structural steel members



Available sizes

Rod size (RS)		Dimension (mm)		Set screw size	Max rec. load (lbs)		Ref. No.
Imperial	Metric	A	B		Top	Bottom	
3/8"	M10	32	44	3/8" (M10)	500	250	P6201 (UL/FM)
1/2"	M12	32	44	1/2" (M12)	950	/	P6202 (UL/FM)

Note:

1. The 3/8" RS version is reversible and suitable for attachment to both top and bottom beam flanges. The 1/2" RS version is for top flange only.
2. Set screw must be tightened onto the sloped side of the beam flange. Follow recommended torque values per MSS SP-69.
3. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.