


Steel C-clamp



- Certificate: UL Listed / FM Approved
- Standard: UL 203, MSS SP-58 (Type 23), MSS SP-69
- Material: Carbon steel, with hardened steel cup-point set screw and locknut
- Surface: Plain / electro-galvanized
- Application: Attach to bottom flanges of structural steel members


Available sizes

Rod size (RS)		Dimension (mm)		Set screw size	Max rec. load (lbs)	Ref. No.
Imperial	Metric	A	B			
3/8"	M10	19	55	3/8" (M10)	400	P6501 (UL/FM)
1/2"	M12	19	58	1/2" (M12)	500	P6502 (UL)

Note:

1. Set screw must be tightened onto the sloped side of the beam flange. Follow recommended torque values per MSS SP-69.
2. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.

Purlin clamp



- Certificate: UL Listed / FM Approved
- Standard: UL 203, MSS SP-58 (Type 23), MSS SP-69
- Material: Malleable iron, with hardened steel cup-point set screw and locknut
- Surface: Plain / electro-galvanized
- Application: Attach to the lower flange of C-purlins and Z-purlins

Available sizes

Rod size (RS)		Dimension (mm)		Set screw size	Max rec. load (lbs)	Ref. No.
Imperial	Metric	A	B			
3/8"	M10	88	72	3/8" (M10)	400	P6601 (UL/FM)

Note:

1. It supports both 45° flanges up to 2" long, and 90° flanges up to 1-1/2" high.
2. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.