


## Brass swing check valve




- Certificate: ISO
- Material: Brass
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: -20°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass



### Available size

Size		Dimension (mm)		Connection	Working pressure	Ref. No.
Inch	DN	L	H			
1/2"	15	50	35	BSPP (G) / BSPT / NPT	PN 16	VC1301
3/4"	20	60	40	BSPP (G) / BSPT / NPT	PN 16	VC1302
1"	25	74	47	BSPP (G) / BSPT / NPT	PN 16	VC1303
1-1/4"	32	84	53	BSPP (G) / BSPT / NPT	PN 16	VC1304
1-1/2"	40	94	60	BSPP (G) / BSPT / NPT	PN 16	VC1305
2"	50	114	70	BSPP (G) / BSPT / NPT	PN 16	VC1306
2-1/2"	65	146	86	BSPP (G) / BSPT / NPT	PN 16	VC1307
3"	80	165	102	BSPP (G) / BSPT / NPT	PN 16	VC1308
4"	100	192	122	BSPP (G) / BSPT / NPT	PN 16	VC1309

## Brass spring check valve



- Certificate: ISO
- Material: Brass, silicone rubber disc
- Connection: Thread, BSPP (G) / BSPT / NPT
- Temperature: -20°C to 150°C
- W. pressure: PN 16 (1.6 MPa)
- Start pressure: 0.4 bar (0.04 MPa)
- Surface: Rough brass



### Available size

Size		L (mm)	Connection	Working pressure	Ref. No.
Inch	DN				
1/2"	15	59	BSPP (G) / BSPT / NPT	PN 16	VC1401
3/4"	20	67	BSPP (G) / BSPT / NPT	PN 16	VC1402
1"	25	74	BSPP (G) / BSPT / NPT	PN 16	VC1403
1-1/4"	32	86	BSPP (G) / BSPT / NPT	PN 16	VC1404
1-1/2"	40	93	BSPP (G) / BSPT / NPT	PN 16	VC1405
2"	50	108	BSPP (G) / BSPT / NPT	PN 16	VC1406
2-1/2"	65	115	BSPP (G) / BSPT / NPT	PN 16	VC1407
3"	80	128	BSPP (G) / BSPT / NPT	PN 16	VC1408
4"	100	151	BSPP (G) / BSPT / NPT	PN 16	VC1409