


Socket weld x threaded tee



- Certificate: ISO
- Standard: Refer to ASME B16.11
- Material: Forged carbon steel ASTM A105
Forged SS ASTM A182, F304 / F316L
- Thread: NPT / BSPT
- W. pressure: Class 3000 / 6000 / 9000
(Class 2000 / 3000 / 6000)
- Surface: Oiled / hot dip galvanized
Pickling white, etc.



Available size

Size			Socket bore dia.	Outside dia. of band H (mm)			Ref. No.
NPS	DN	OD (mm)	B (mm)	Class 2000	Class 3000	Class 6000	
1/2"	15	21.3	21.8 ~ 22.2	33	38	46	N3601
3/4"	20	26.7	27.2 ~ 27.6	38	46	56	N3602
1"	25	33.4	33.9 ~ 34.3	46	56	62	N3603
1-1/4"	32	42.2	42.7 ~ 43.1	56	62	75	N3604
1-1/2"	40	48.3	48.8 ~ 49.2	62	75	84	N3605
2"	50	60.3	61.2 ~ 61.7	75	84	102	N3606
2-1/2"	65	73.0	73.9 ~ 74.4	92	102	121	N3607
3"	80	88.9	89.8 ~ 90.3	109	121	146	N3608
4"	100	114.3	115.2 ~ 115.7	146	152	152	N3609