


Ceiling flange



- Certificate: UL Listed / FM Approved
- Standard: NFPA 13 compliant
- Material: Malleable iron
- Surface: Plain / electro-galvanized / copper plated / epoxy coating
- Application: Secure hanger rods to wood beams, concrete ceilings, or walls


Available sizes

Rod size (RS)		Mounting hole	Height (H)	Length (L)	Max rec. load (lbs)	Ref. No.
Imperial	Metric					
3/8"	M10	5/16" (2 holes)	1-3/8"	2-3/4"	180	P6901 (UL/FM)
1/2"	M12	5/16" (2 holes)	1-3/8"	2-3/4"	180	P6902 (UL)

Note:

1. Use appropriate wood screws, lag screws, or concrete anchors through the mounting holes.
2. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.

Side beam bracket



- Certificate: UL Listed
- Standard: UL 203, MSS SP-58 (Type 34), MSS SP-69
- Material: Carbon steel
- Surface: Pre-galvanized
- Application: Secure hanger rod to the vertical face of wood beams, steel beams, or concrete walls

Available sizes

Rod size (RS)		Mounting hole 1	Mounting hole 2	Length (L)	Max rec. load (lbs)	Ref. No.
Imperial	Metric					
3/8"	M10	17/32"	13/32"	2-9/16"	560 (620)	P7001 (UL)
1/2"	M12	17/32"	13/32"	2-9/16"	560 (620)	P7002 (ISO)

Note:

1. 560 lbs when secured with lag screw to wood beam; 620 lbs when bolted directly to steel beam.
2. Maximum recommended loads are based on normal ambient temperatures and include a minimum safety factor of 5:1 per MSS SP-58.

P69-P70 /