

Adjustable I-Beam adapter



- Certificate: UL Listed / FM Approved
- Standard: UL 203A, NFPA 13
- Material: Carbon steel
- Surface: Electro-galvanized
- Installation: Horizontal and vertical
- Application: Attach to wide range of I-beam flanges (top/bottom)




Available sizes

I-Beam flange thickness	I-Beam width (A)	Mounting bolt (S1)	Tie rods size (S2)	UL rated load (lbs)	FM rated load - Lateral (lbs)		Ref. No.
					30° ~ 44°	75° ~ 90°	
1/4" ~ 3/4"	4" ~ 8.5"	1/2"	3/8"	1500 / 1700*	1180	2940	P7301 (UL/FM)
1/4" ~ 3/4"	4" ~ 14.5"	1/2"	3/8"	1500 / 1700*	1180	2940	P7302 (UL/FM)
3/4" ~ 1-1/4"	4" ~ 18"	1/2"	3/8"	1700	1220	2870	P7303 (UL/FM)

Note:

1. UL Listed and FM Approved when the brace member is steel pipe NPS 1" ~ 2" SCH40. UL rated loads: 1500 lbs (1/4" ~ 5/16" flange), 1700 lbs (3/8" ~ 3/4" flange). FM lateral loads as shown – for longitudinal loads or brace angles 45° ~ 74°, consult TPMC.
2. This adapter can also be used as a cable structural attachment fitting for non-rigid sway brace systems.

Multi attachment (Multi-fastener adapter)



- Certificate: UL Listed / FM Approved
- Standard: UL 203A, NFPA 13
- Material: Carbon steel
- Surface: Electro-galvanized
- Installation: Horizontal and vertical
- Application: Attach to concrete and wood structures



Available sizes

Hole size 1 (HS1)	Hole size 2 (HS2)	Dimension (mm)		UL rated load (lbs)	FM rated load (lbs)		Ref. No.
		A	B		30° ~ 44°	75° ~ 90°	
9/16" (2 holes)	9/16" (1 hole)	305	64	680	3290	6200	P7401 (UL/FM)
13/16" (2 holes)	9/16" (1 hole)	305	64	680	3290	6200	P7402 (UL/FM)

Note: UL Listed and FM Approved when the brace member is steel pipe NPS 1" ~ 2" SCH40. FM rated loads (both lateral and longitudinal) as shown - for brace angles 45° ~ 74°, consult TPMC.