

Universal restraint clip



- Certificate: UL Listed
- Standard: UL 203A, NFPA 13
- Material: Carbon steel
- Surface: Electro-galvanized
- Bracing: Lateral and longitudinal direction
- Application: Attach seismic sway brace cable to building structure

Available sizes

Fastener size	Feature	Cable size range	UL rated load (lbs)	Ref. No.
3/8" (M10)	Two eyelets	3/32", 1/8", 3/16"	418, 772, 1909	P7801 (UL)
1/2" (M12)	Two eyelets	3/32", 1/8", 3/16"	418, 772, 1909	P7802 (UL)
5/8" (M16)	Two eyelets	3/32", 1/8", 3/16"	418, 772, 1909	P7803 (UL)

Note: UL rated load is based on the specific cable size used. The non-rigid assembly must not be loaded beyond the rating of its weakest component.

No-pry clip



- Certificate: UL Listed
- Standard: UL 203A, NFPA 13
- Material: Carbon steel
- Surface: Electro-galvanized
- Bracing: Lateral and longitudinal direction
- Application: Attach seismic sway brace cable to building structure

Available sizes

Fastener size	Feature	Cable size range	UL rated load (lbs)	Ref. No.
3/8" (M10)	Curved edge	3/32", 1/8", 3/16"	418, 772, 1909	P7901 (UL)
1/2" (M12)	Curved edge	3/32", 1/8", 3/16"	418, 772, 1909	P7902 (UL)

Note: UL rated load is based on the specific cable size used. The non-rigid assembly must not be loaded beyond the rating of its weakest component.