


Rubber covered fire hose

Rubber covered fire hose from TPMC is engineered for heavy-duty municipal firefighting operations, serving as attack line, relay supply hose, and feeder line for master stream appliances such as deck guns and monitor nozzles. The rugged rubber outer cover delivers exceptional resistance to abrasion, chemicals, oil, extreme temperatures, and soiling, while remaining flexible and completely maintenance-free. This eliminates drying time between calls and ensures reliable performance in the harshest fireground environments.



- Certificate: UL Listed / FM Approved
- Standard: UL 19, NFPA 1961 / 1962
- Feature: Abrasion resistant, maintenance free, ozone-resistant
- Color: Red, yellow, or custom
- Temperature: -40°C to 80°C



Main parts and material

Lining	Smooth, extruded nitrile rubber (NBR), low friction loss	Jacket (Reinforcement)	Circular woven 100% high-tenacity polyester, completely embedded thru-the-weave
Cover	Heavy-duty ribbed nitrile/PVC blend, superior abrasion resistance and grip	Coupling	Brass or aluminum, rocker lug swivel NH (NST), or storz

Available size (Source 1 with UL)

Size	Type	Lining	Length (feet)	Service pressure (psi)	Proof pressure (psi)	Burst pressure (psi)	Ref. No.
1-1/2"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	300	600	900	F4301 (UL)
1-3/4"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	300	600	900	F4302 (UL)
2"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	300	600	900	F4303 (UL)
2-1/2"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	300	600	900	F4304 (UL)
3"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	300	600	900	F4305 (UL)
4"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	250	500	750	F4306 (UL)
5"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	250	500	750	F4307 (UL)
6"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	200	400	600	F4308 (ISO)

Note: The couplings are pre-assembled on both ends of fire hose, with NST type or Storz type.

Rubber covered fire hose

Available size (Source 2 with UL/FM)

Size	Type	Lining	Length (feet)	Service pressure (psi)	Proof pressure (psi)	Burst pressure (psi)	Ref. No.
1-1/2"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	200	400	600	F4311 (UL/FM)
2-1/2"	Rubber covered	Nitrile rubber (NBR)	50 / 75 / 100	200	400	600	F4312 (UL)

Note: The NST couplings are pre-assembled on both ends of fire hose through expansion rings.