


Grooved 45° elbow



- Certificate: UL Listed / FM Approved
- Standard: ANSI / UL 213C
- Material: Ductile iron ASTM A536, 65-45-12
Stainless steel ASTM A312 304 / 316
- Rated pressure: 300 ~ 500 psi
- Surface: Red painting / hot dip galvanized
SS 304 / SS 316



Available size

Size			Center to end	Ref. No.
Inch	DN	mm	L (mm)	
1"	25	33.7	45	G0701 (UL/FM)
1-1/4"	32	42.4	45	G0702 (UL/FM)
1-1/2"	40	48.3	45	G0703 (UL/FM)
2"	50	60.3	51	G0704 (UL/FM)
2-1/2"	65	73.0	57	G0705 (UL/FM)
2-1/2"	65	76.1	57	G0706 (UL/FM)
3"	80	88.9	64	G0707 (UL/FM)
4"	100	114.3	76	G0708 (UL/FM)
5"	125	139.7	83	G0709 (UL/FM)
5"	125	141.3	83	G0710 (UL/FM)
6"	150	165.1	89	G0711 (UL/FM)
6"	150	168.3	89	G0712 (UL/FM)
8"	200	219.1	108	G0713 (UL/FM)
10"	250	273.0	121	G0714 (UL/FM)
12"	300	323.9	133	G0715 (UL/FM)

Grooved 45° elbow

Available size

Inch	Size		Center to end	Ref. No.
	DN	mm	L (mm)	
14"	350	355.6	152	G0716 (UL)
16"	400	406.4	184	G0717 (UL)
18"	450	457.2	203	G0718 (UL)
20"	500	508	229	G0719 (UL)
24"	600	609.6	280	G0720 (UL)