Elbow outlet

- Certificate: ISO
- Standard: MSS SP-97, GB/T 19326
- Material: Carbon steel ASTM A234, WPB
  SS ASTM A403, WP304 / WP316L
- Connection: Socket weld, threaded, butt weld
- W. pressure: Class 3000 / 6000, or equal to same seamless pipe
- Surface: Oiled / hot dip galvanized
  Pickling white, etc.



Available size with SW and THD

Branch outlet size			Length A (mm)		Connection	Ref. No.
NPS	DN	OD (mm)	Class 3000	Class 6000		
1/2"	15	21.3	38 ~ 45	46 ~ 54	SW, NPT, BSPT	N7601
3/4"	20	26.7	46 ~ 51	54 ~ 62	SW, NPT, BSPT	N7602
1"	25	33.4	54 ~ 62	61 ~ 70	SW, NPT, BSPT	N7603
1-1/4"	32	42.2	61 ~ 69	65 ~ 75	SW, NPT, BSPT	N7604
1-1/2"	40	48.3	64 ~ 72	79 ~ 89	SW, NPT, BSPT	N7605
2"	50	60.3	76 ~ 84	90 ~ 105	SW, NPT, BSPT	N7606
2-1/2"	65	73.0	85 ~ 95	/	SW, NPT, BSPT	N7607
3"	80	88.9	97 ~ 110	/	SW, NPT, BSPT	N7608
4"	100	114.3	125 ~ 140	/	SW, NPT, BSPT	N7609

Elbow outlet

Available size with BW

Branch outlet size			Length A (mm)		Connection	Ref. No.
NPS	DN	OD (mm)	STD	XS		
1/2"	15	21.3	38	43	BW	N7611
3/4"	20	26.7	45	51	BW	N7612
1"	25	33.4	54	65	BW	N7613
1-1/4"	32	42.2	54	65	BW	N7614
1-1/2"	40	48.3	64	75	BW	N7615
2"	50	60.3	73	89	BW	N7616
2-1/2"	65	73.0	95	110	BW	N7617
3"	80	88.9	115	130	BW	N7618
4"	100	114.3	140	155	BW	N7619
5"	125	141.3	170	185	BW	N7620
6"	150	168.3	195	210	BW	N7621
8"	200	219.1	220	235	BW	N7622
10"	250	273.0	250	265	BW	N7623
12"	300	323.8	280	295	BW	N7624
14"	350	355.6	300	320	BW	N7625
16"	400	406.4	330	350	BW	N7626
18"	450	457	370	390	BW	N7627
20"	500	508	410	430	BW	N7628
24"	600	610	490	515	BW	N7629