


K25.2 CMSA standard response pendent sprinkler

K25.2 CMSA (Control mode specific application) sprinkler produces large water droplet and provides fire control for specific high-challenge fire hazards using discharge pressures and areas criteria in NFPA 13 and FM Specification.



- Certificate: UL Listed / FM Approved
- Standard: UL 199, NFPA 13
- Feature: K25.2 (K363), CMSA, SR, pendent
- W. pressure: 175 psi
- T. pressure: 500 psi, factory hydrostatic test
- O. pressure: Min 7 psi
- Surface: Rough brass



Main parts and material

Deflector	Bronze	Heat responsive element	Fusible alloy, nickel link assembly
Frame	Brass	Seal	Teflon tape

Available size

Type	Nominal K-Factor	Response type	Temperature rating	Connection	Working pressure (psi)	Ref. No.
Storage CMSA pendent	K25.2 (K363)	Standard (SR)	162°F (72°C)	1", NPT or BSPT	175	S7901 (UL/FM)
Storage CMSA pendent	K25.2 (K363)	Standard (SR)	212°F (100°C)	1", NPT or BSPT	175	S7902 (UL/FM)
Storage CMSA pendent	K25.2 (K363)	Standard (SR)	286°F (141°C)	1", NPT or BSPT	175	S7903 (UL/FM)