Recessed escutcheon

- Certificate: UL Listed / FM Approved
- Standard: UL 199, NFPA 13
- Material: Carbon steel / SS
- Surface: Chromed plated / white paint

Available size

Type	Material	Sprinkler thread size	Adjustment	Overall diameter	Ref. No.
Two-piece	Carbon steel / SS	1/2"	3/4" (19.1 mm)	2-7/8" (73 mm)	S9601 (UL/FM)
Two-piece	Carbon steel / SS	3/4"	3/4" (19.1 mm)	2-7/8" (73 mm)	S9602 (UL/FM)
Two-piece	Carbon steel / SS	1/2"	1/2" (12.7 mm)	2-7/8" (73 mm)	S9603 (UL/FM)
Two-piece	Carbon steel / SS	3/4"	1/2" (12.7 mm)	2-7/8" (73 mm)	S9604 (UL/FM)

Note: The escutcheon are certified for use with UL listed / FM approved sprinklers of different brands.

Flush escutcheon

- Certificate: ISO
- Standard: UL 199, NFPA 13
- Material: Carbon steel / plastic
- Surface: Chromed plated / white paint / white plastic

Available size

Type	Material	Sprinkler thread size	Height	Overall diameter	Ref. No.
One-piece	Carbon steel	1/2"	1/2" (12.7 mm)	2-13/16" (71.4 mm)	S9611 (ISO)
One-piece	Carbon steel	3/4"	1/2" (12.7 mm)	2-13/16" (71.4 mm)	S9612 (ISO)
One-piece	Carbon steel	1/2"	1/4" (6.4 mm)	3" (76.2 mm)	S9613 (ISO)
One-piece	Carbon steel	3/4"	1/4" (6.4 mm)	3" (76.2 mm)	S9614 (ISO)
One-piece	Carbon steel	1''	16 mm	75 mm	S9615 (ISO)
Two-piece	Plastic (PP)	1/2"	6.5 mm	80 mm	S9616 (ISO)
Two-piece	Plastic (PP)	3/4"	6.5 mm	85 mm	S9617 (ISO)
Two-piece	Plastic (PP)	1"	6.5 mm	95 mm	S9618 (ISO)
Two-piece	Plastic (PP)	1-1/4"	6.5 mm	105 mm	S9619 (ISO)
Two-piece	Plastic (PP)	1-1/2"	6.5 mm	115 mm	S9620 (ISO)