


Sprinkler cabinet

Sprinkler cabinet is constructed of body, holed shelf and hinged covers. And it provides onsite storage of an emergency supply of sprinklers and a sprinkler wrench.



- Certificate: ISO
- Capacity: 6 ~ 24 pcs sprinklers
- Body: Heavy gauge steel
- Thickness: Refer to Body 0.8 mm, cover 1.1 mm
- Finish: Red enamel



Available size

Type	Structure	W (mm)	H (mm)	D (mm)	Ref. No.
For 6 standard sprinklers	K5.6, K8.0, K11.2	360	160	80	S9901 (ISO)
For 12 standard sprinklers	K5.6, K8.0	360	160	160	S9902 (ISO)
For 24 standard sprinklers	K5.6, K8.0	360	320	160	S9903 (ISO)
For 6 large sprinklers	Concealed, ESFR, guard	364	165	80	S9904 (ISO)

Note: Additional sprinkler wrench is optional. Please see our catalog S98 series if need.

Sprinklers in building (pcs)	Min spare sprinkler (pcs)	As NFPA 13 and 13R, it requires spare of each type of sprinkler used in a sprinkler system to be stored in a cabinet onsite so for immediate removal and replacement that may have operated or become damaged.
Under 300	6	
300 ~ 1000	12	
Over 1000	24	

Note: When the sprinkler system includes more than one type of temperature rating sprinklers, the stock of spare sprinklers must include a proportional sampling of each type and temperature rating; however, a minimum of 3 each is recommended.