
Brass pressure relief valve






- Certificate: ISO
- Material: Brass
- Connection: Threaded, Male x Female and Female x Female
- Adjustment: 3 / 6 / 8 bar
- Temperature: 0°C to 80°C
- W. pressure: PN 16 (1.6 MPa)
- Surface: Rough brass

Available size

Size		Relief pressure (Bar)	Dimension (mm)			Connection	Working pressure	Ref. No.
Inch	DN		L	H	B			
1/2"	15	3	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2301
1/2"	15	6	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2302
1/2"	15	8	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2303
3/4"	20	3	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2304
3/4"	20	6	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2305
3/4"	20	8	61	29	22	BSPP (G) / BSPT / NPT	PN 16	VC2306

Brass threaded adapter



- Certificate: ISO
- Material: Brass
- Connection: Threaded, Female x Male
- W. pressure: 300 psi
- Surface: Rough brass

Available size

Size		Connection	Working pressure (psi)	Ref. No.
NPS	DN			
1/4"	8	BSPT F x NPT M, BSPP F x NPT M	300	VC2401 (ISO)
1/2"	15	BSPT F x NPT M, BSPP F x NPT M	300	VC2402 (ISO)
3/4"	20	BSPT F x NPT M, BSPP F x NPT M	300	VC2403 (ISO)
1"	25	BSPT F x NPT M, BSPP F x NPT M	300	VC2404 (ISO)