


Bronze Y type strainer




- Certificate: ISO
- Material: Bronze
- Connection: Thread, BSPP (G) / BSPT / NPT
- Screen: Standard 18 mesh
- Temperature: -20°C to 180°C
- W. pressure: PN 20, or PN 25 (Only BSPT)
- Surface: Rough bronze

Available size

Size		L (mm)	Mesh screen	Connection	Working pressure	Ref. No.
Inch	DN					
1/2"	15	58	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3501
3/4"	20	70	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3502
1"	25	82	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3503
1-1/4"	32	93	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3504
1-1/2"	40	104	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3505
2"	50	125	18	BSPP (G) / BSPT / NPT	PN 20 / 25	VC3506
3"	80	240	18	BSPP (G) / BSPT / NPT	PN 20	VC3507

3-way bronze globe valve (Gauge valve)



- Certificate: UL Listed
- Material: Bronze
- Connection: Thread, BSPT / NPT
- Temperature: -20°C to 180°C
- W. pressure: 600 / 175 / 300 psi
- Surface: Rough bronze

Available size

Size		Dimension (mm)			Connection	Working pressure (psi)	Ref. No.
Inch	DN	L	H	D			
1/4"	8	42	50	54	BSPT / NPT	600	VC3601 (UL)
1/4"	8	44	55	53	BSPT / NPT	175	VC3602 (UL)
1/4"	8	42	64	56	BSPT / NPT	300	VC3603 (ISO)