


Lockable pressure relief valve



- Certificate: UL Listed / FM Approved
- Standard: NFPA 13
- Material: Bronze body, SS spring and plastic casing
- Connection: Thread, NPT
- W. pressure: 300 psi




Available size

Size		Relief pressure range (psi)	A	Connection	Working pressure (psi)	Ref. No.
Inch	DN		mm			
1/2"	15	175 ~ 300	90	NPT, M X F	300	VC3901 (UL/FM)
3/4"	20	175 ~ 300	98	NPT, M X F	300	VC3902 (UL/FM)

Note:

1. For 1/2", UL listed relief pressure setting is 175 ~ 220 psi, 225 ~ 295 psi and 300 psi; FM approved relief pressure setting is 175 ~ 300 psi.
2. For 3/4", UL listed relief pressure setting is 175 ~ 220 psi; FM approved relief pressure setting is 175 ~ 300 psi.

Adjustable pressure relief valve



- Certificate: FM Approved
- Standard: NFPA 13
- Material: Bronze body, SS spring
- Connection: Thread, NPT
- W. pressure: 310 psi



Available size

Size		Relief pressure range (psi)	A	Connection	Working pressure (psi)	Ref. No.
Inch	DN		mm			
1/2"	15	175 ~ 310	94	NPT, M X F	310	VC3911 (FM)
3/4"	20	175 ~ 310	98	NPT, M X F	310	VC3912 (FM)
1"	25	175 ~ 310	105	NPT, M X F	310	VC3913 (FM)